# Electrical Substation Safaniyah, Kingdom of Saudi Arabia



#### **Project Location:**

Safaniyah, Saudi Arabia

#### **Main Contractor:**

Larsen & Toubro Saudi Arabia LLC, Al Khobar

#### Contractor:

Foundations Building Contracting Co. Ltd. (FBCC)

#### Owner:

**ARAMCO** 

#### **Project period**

Dec. 2015

#### Method Applied:

600 Top Feed (Vibro Replacement) Stone Columns of in average 0.80 m diameter installed in a triangular grid of 2.0 m to a maximum depth of 8 m.

### **Betterground GmbH**

Hassenham 8 D-84419 Schwindegg Germany

Tel: +49-8082-2713135 Tel: +49-89-76776194-0 Fax: +49-89-76776194-20


Email: <u>info@betterground.com</u>
Web: <u>www.betterground.com</u>

## **Technical Requirements:**

Stone columns to found an electrical substation on a 972  $m^2$  raft. Reduce total and differential settlement under a distributed load of 165 kN/ $m^2$ .








Digital QC data output from rig, showing Depth (red), Amperage (green) and Gravel. Batch placement (black step curve).


The above installation protocol shows a custom work method developed to achieve both the feeding of gravel throughout the full length of the column as well as the compaction of all sand layers with lesser fines content than 10 %. Holding of the vibroflot at certain depth intervals heips to achieve optimal compaction of the cleaner sand layers. The here shown method cannot be generalized, but has to be developed specifically for each site. This makes the expertise of Betterground's Vibro Experts so valuable.


## **Quality Control Testing:**


8 Electronic Cone Penetration Tests (CPTs), supported by digital process data from Vibro rigs.

2 Full Scale Plate Load Tests (BS 1377, Part 9)









Settlement of a 2.0 m x 2.0 m plate under a maximum load of  $165 \text{ kN/m}^2$ .